

DEVICES AND METHODS FOR OPTICAL DETECTION OF NUCLEIC ACID HYBRIDIZATION

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS

*Dkt
011*

[0001] This application is a divisional of co-pending application Serial No. 09/425,072 filed October 22, 1999, which is a continuation of co-pending application Serial No. 08/374,151 filed January 17, 1995, which is a Continuation in part of US Application 07/965,661, filed September 17, 1992, now abandoned, which is a continuation of U.S. Serial No. 07/260,317, filed October 20, 1998, now abandoned, which is a continuation of U.S. Serial No. 06/832,628, filed February 25, 1986, now abandoned, which is entitled to foreign priority from West German Application No. P3506703.9-52, filed February 26, 1985, entitled "A Method of Sequence Analysis of Nucleic Acids in Particular Deoxyribonucleic Acid (DNA) and Ribonucleic Acid (RNA), As Well As A Support for Performing the Method and A Method for Producing the Support," each of which is hereby incorporated in their entirety herein, including all drawings, tables and claims.

FIELD OF THE INVENTION

[0002] The present invention relates generally to fields using devices and methods for detecting nucleic acid hybridization.

The following is a discussion of relevant art, none of which is admitted to be prior art to the appended claims.

Methods to amplify either the number of copies of the nucleic acid available for detection or the signal generated after hybridization of the nucleic acid probe have been utilized. A review of nucleic acid based detection methods and various amplification schemes such as polymerase chain reaction (PCR), ligase chain reaction (LCR), transcription based amplification, cycling probe reaction, Q β replicase, and strand displacement amplification may be found in M.J. Wolcott, *Clinical Microbiology Reviews*, 5, Oct. 1992, pp 370 - 386.

U.S. Patent 5,175,270 describes an amplification reagent consisting of layers of nucleotide polymers containing double stranded and single stranded sections. Each section has an end which is capable of hybridizing with another molecule.

Probe or hybridization assays are often based on the attachment of an oligonucleotide probe to a surface in order to capture a target nucleic acid molecule (analyte) from a sample. The attachment of this probe to the surface may be through covalent bonds or through a variety of passive absorption mechanisms (e.g., hydrophobic or ionic interactions).

U.S. Patent 5,279,955 describes an immobiliza-
35 tion process which uses a heterofunctional cross-linker
for a plastic support. The cross-linker consists of a
central ring which is hydrophobic and interacts with the

plastic, and a hydrophilic chain which terminates in a group capable of reacting with a nucleic acid. Covalent attachment is achieved through a succinyl-olivetol-N-hydroxysuccinimide.

5 U.S. Patent 5,262,297 describes immobilization of a probe through co-polymers which contain reactive carboxylic acid groups and an 8-50 atom spacer with two or more unsaturated groups within the spacer.

10 U.S. Patent 5,034,428 describes an immobilization process for probes in which a monomer is joined onto a hydrophilic solid support which can be irradiated in an oxygen free atmosphere. This method provides for covalent attachment of the probe.

15 U.S. Patent 4,806,546 also describes an immobilization process for an amide modified nylon. The method relies on an amidine linkage under anhydrous conditions in the presence of an alkylating agent.

Maskos and Southern, 20 Nucleic Acids Research 1679, 1992, describe a linker system for the attachment of a nucleic acid to a glass support. The linker system allows for the chemical synthesis of a strand of nucleic acids on the surface. The primary advantage of the linker is that it is stable to an ammonia treatment which is required in the synthesis of the polynucleotide. A
25 hexaethylene glycol spacer is incorporated into the linker which attaches to the glass through a glycidoxypropyl silane which terminates in a primary hydroxy group. The silane is condensed onto silane groups on a solid support. Additional cross-linking may be obtained by introducing
30 water so that the epoxide group is cleaved to a diol. An acidic solution facilitates this process. The length of the linker may be varied by changing the spacer to ethylene glycol, pentaethylene glycol, etc.

35 Nucleic acid probes that have hybridized to their target sequence are detected based on various methods that introduce a detectable chemiluminescent, fluorescent or other identifiable label into a nucleic

acid probe. Several of these techniques are described in U.S. Patents 4,968,602, 4,818,680, 5,104,791, and 5,272,056, and International applications WO91/00926 and GB2169403A.

5 Arnold et al., U.S. Patent 5,283,174 describe the use of a chemiluminescent label with DNA probes. The label is composed of an acridinium ester and has a number of desirable properties. It is stable to hybridization conditions, light is emitted only upon exposure to an
10 alkaline peroxide, the emission kinetics are rapid, and the label on the unhybridized probe can be destroyed without an impact on the signal generated by hybridized probe.

15 U.S. Patent 5,089,387 describes a diffraction assay for the detection of DNA hybridization. In this invention, a solid support, generally silicon or polysilicon, is coated with a DNA probe. These surfaces are required to inherently adhere the DNA probe to the surface. Once the surface is coated with the probe, the
20 surface is selectively inactivated to provide a series of very strictly controlled reactive probe lines for the generation of the diffraction grating. The unreacted surface is required to be non-light disturbing. The diffraction grating is only generated upon the addition of
25 the analyte to the surface. The angle of diffraction is a function of the wavelength of incident light and the density and spacing of the individual gratings on the surface. A single detector or a multiple detector array may be used to detect and measure the light from all
30 desired orders of the diffracted light.

Mixed phase systems have typically been used to perform hybridization assays. In mixed phase assays the hybridizations are performed on a solid phase such as nylon or nitrocellulose membranes. For example, the
35 assays usually involve loading a membrane with a sample, denaturing the DNA or creating single stranded molecules, fixing the DNA or RNA to the membrane, and saturating the

remaining membrane attachment sites with heterologous nucleic acids to prevent the probe reagent from adhering to the membrane in a non-specific manner. All of these steps must be carried out before performing the actual hybridization.

SUMMARY OF THE INVENTION

This invention features improved devices, and methods for producing and using optical devices, for detecting the presence or amount of a specific target nucleic acid within a sample. The current invention is based on a probe coated substrate which is optically active. Surfaces can be pre-selected for the type of optical thin film detection to be employed, and enable direct detection of the hybridization reaction through the interaction of light with thin films. Detection of specific target nucleic acid sequences is also referred to as sequence analysis.

This invention also describes materials and methods for producing optically active solid supports or devices for use in nucleic acid hybridization assays and immobilization of nucleic acid probes to such surfaces. These surfaces are compatible with a wide range of optical thin film detection methods, all of which utilize some interaction of thin films with light. Such optical thin film detection methods include optical interference, ellipsometry - comparison, null, photometric and other modifications, attenuation of polarized light at non-Brewster angles, profilometry, scanning tunneling microscopy, surface plasmon resonance, evanescent wave techniques, reflectometry, or atomic force microscopy.

The direct optical thin film detection methods of the current invention are extremely sensitive to changes in mass at the surface of an optically active substrate. These optical thin film detection methods provide increased sensitivity for hybridization assays without the introduction of signal generating labels or

pre-assay target amplification with its accompanying complexity and limitations. Thus, assay protocols utilizing optical thin film detection methods are greatly simplified, are more rapid, and less costly than conventional indirect assay methods. Total assay times may vary from one hour to a few minutes from the initiation of the assay protocol (i.e., from the time that the target nucleic acid containing sample is contacted with the device). Such devices also allow for assay results to be visualized as a color change or detected by instrumented formats.

The methods and devices of the claimed invention by concentrating on improving characteristics of the surface immobilized probe and detection of the hybridization reaction without the use of a labelled component allow for rapid, convenient, and sensitive assays for diagnostic (routine clinical) and research use.

In a first aspect the invention features an optical assay device for detecting the presence or amount of a target nucleic acid. The device includes an optically active substrate capable of producing a thin film effect, and exhibiting a first set of reflective and transmissive properties in response to light impinging thereon, and exhibiting a second set of reflective and transmissive properties different from said first set, in response to light when the target nucleic acid is bound to a target specific capture probe and creates a change in mass on said optically active substrate. The target specific capture probe is attached to an attachment layer that is present on the optically active layer. Detection of the second set of reflective or transmissive properties indicates the presence or amount of the target nucleic acid.

An "optically active substrate" comprises an optically active surface. Such a substrate may consist of more than one layer (multi-layered), for example; base material, a conducting metal layer of aluminum, chromium, or a transparent conducting oxide, and a layer of

amorphous silicon, wherein the metal layer is positioned adjacent the amorphous silicon. Alternatively, the multi-layered substrate may comprise a layer of base material (any solid material on which optically active layers may be applied), and a layer of amorphous silicon adjacent the base material. The base material is selected from any of the group consisting of glass, fused silica, plastics, semiconductors, ceramics, and metals, and may be either rigid or flexible. The optically active surface substrate also serves as a solid support for the nucleic acid target probe and any amplification components (if necessary) and must be chemically stable to the application of the attachment layer, the nucleic acid probe, and all assay reagents. The properties of the optically active substrate are matched to the direct optical thin film detection method employed.

An "optically active surface" is a surface that participates in the generation of an optical effect such that the light impinging upon that surface is in some way altered. Such optically active surfaces may be adapted to respond not only to polychromatic light (e.g., white light) but also to monochromatic light (e.g., laser light, which may be inherently polarized). The optically active surface may be designed to reflect or transmit light. The substrate may inherently possess an optically active surface or the substrate may require an optically active surface be applied to introduce the desired optical characteristics. Thus, the optically active substrate may inherently possess the properties required for a given thin film detection method, or a surface may be modified to provide the required optical properties. Materials which are suitable for optically active substrates include monocrystalline or polycrystalline silicon, glasses, ceramics, metals, amorphous silicon on glass, amorphous silicon on plastic, plastics, and composites of these materials.

By "thin film effect" is meant that light impinging on an optically active surface or substrate is attenuated or modulated in its reflective or transmissive properties.

- 5 The first set of reflective or transmissive properties is defined as a combination of wavelengths of light, or a spectral distribution, or an intensity of one or more of wavelengths, or a degree or amount of elliptical polarization, or an amount of polarization rotation.
- 10 The substrate also exhibits a second set of reflective or transmissive properties which is different from the first set. The second set of reflective or transmissive properties is exhibited in response to the same light when the target nucleic acid is present on the surface. This
- 15 second set of reflective or transmissive properties is due to a change in mass on the optically active substrate. The change from one set of properties to another can be measured either by use of an instrument, or by eye. The optical active substrate is selected to be compatible with
- 20 the method of optical thin film detection.

- The target nucleic acid is selected so that it specifically identifies a single organism or gene. The target sequence is selected such that the stringency of the assay conditions will promote or enhance the specificity of the assay. The target nucleic acid may be a DNA
- 25 or RNA (rRNA, tRNA, mRNA, small nuclear RNA's (SNURPS)) molecule either intact or a fragment thereof covering a range of molecular weights. Fragments may be generated enzymatically, chemically, or by mechanical shearing. The
- 30 target may be free or contained within a larger complex, i.e., complexed with protein(s). The target may be single or double stranded oligonucleotide and the source may be a bacterium, a virus, a human cell, and may be isolated from a culture medium or a biological fluid.

- 35 A "target specific capture probe" refers to a synthetic or biologically produced nucleic acid which by design contains specific, complimentary nucleotide

sequences that allow it to hybridize to a target nucleic acid sequence. The probe may be composed of deoxyribose, ribose, or a combination of these nucleotides (chimera) and may be synthesized chemically, isolated from a biological source, or cloned. It may be a linear strand or may contain branch points to increase the density of immobilized probe. The probe may provide a single or multiple copies of the sequence complimentary to the target nucleic acid. The nucleic acid probe or capture probe is selected to specifically hybridize a target nucleic acid. When more than one probe is used in a hybridization assay, each probe should recognize a unique sequence well separated from each other within the target oligonucleotide.

Hybridization is the process by which two partially or completely complementary strands of nucleic acid are allowed to come together, under predetermined reaction conditions, in an antiparallel fashion to form double stranded nucleic acid with specific and stable hydrogen bonds. The nucleic acid capture probe sequence is selected to specifically interact with the target molecule or analyte at a pre-determined degree of stringency. The probe length is pre-determined to provide the required specificity at the degree of stringency used in the assay. Assay conditions are set so that the stringency of hybridization between the capture probe and the target nucleic acid provides the required specificity.

Stringency of a particular set of hybridization conditions is defined by the length and base composition of the probe/target duplex as well as by the amount and geometry of mispairing between the two nucleic acids. It is governed by such solution parameters as concentration and type of ionic species, type and concentration of denaturing agents, precipitating agents, and the temperature of hybridization. As stringency increases, longer probes are preferred for the generation of stable hybrids. The stringency of the reaction conditions control the specificity of a hybridization assay. For a complete review of

1. Mr. J. H. Smith
 2. Mr. J. H. Smith
 3. Mr. J. H. Smith
 4. Mr. J. H. Smith
 5. Mr. J. H. Smith
 6. Mr. J. H. Smith
 7. Mr. J. H. Smith
 8. Mr. J. H. Smith
 9. Mr. J. H. Smith
 10. Mr. J. H. Smith
 11. Mr. J. H. Smith
 12. Mr. J. H. Smith
 13. Mr. J. H. Smith
 14. Mr. J. H. Smith
 15. Mr. J. H. Smith
 16. Mr. J. H. Smith
 17. Mr. J. H. Smith
 18. Mr. J. H. Smith
 19. Mr. J. H. Smith
 20. Mr. J. H. Smith
 21. Mr. J. H. Smith
 22. Mr. J. H. Smith
 23. Mr. J. H. Smith
 24. Mr. J. H. Smith
 25. Mr. J. H. Smith
 26. Mr. J. H. Smith
 27. Mr. J. H. Smith
 28. Mr. J. H. Smith
 29. Mr. J. H. Smith
 30. Mr. J. H. Smith
 31. Mr. J. H. Smith
 32. Mr. J. H. Smith
 33. Mr. J. H. Smith
 34. Mr. J. H. Smith
 35. Mr. J. H. Smith
 36. Mr. J. H. Smith
 37. Mr. J. H. Smith
 38. Mr. J. H. Smith
 39. Mr. J. H. Smith
 40. Mr. J. H. Smith
 41. Mr. J. H. Smith
 42. Mr. J. H. Smith
 43. Mr. J. H. Smith
 44. Mr. J. H. Smith
 45. Mr. J. H. Smith
 46. Mr. J. H. Smith
 47. Mr. J. H. Smith
 48. Mr. J. H. Smith
 49. Mr. J. H. Smith
 50. Mr. J. H. Smith
 51. Mr. J. H. Smith
 52. Mr. J. H. Smith
 53. Mr. J. H. Smith
 54. Mr. J. H. Smith
 55. Mr. J. H. Smith
 56. Mr. J. H. Smith
 57. Mr. J. H. Smith
 58. Mr. J. H. Smith
 59. Mr. J. H. Smith
 60. Mr. J. H. Smith
 61. Mr. J. H. Smith
 62. Mr. J. H. Smith
 63. Mr. J. H. Smith
 64. Mr. J. H. Smith
 65. Mr. J. H. Smith
 66. Mr. J. H. Smith
 67. Mr. J. H. Smith
 68. Mr. J. H. Smith
 69. Mr. J. H. Smith
 70. Mr. J. H. Smith
 71. Mr. J. H. Smith
 72. Mr. J. H. Smith
 73. Mr. J. H. Smith
 74. Mr. J. H. Smith
 75. Mr. J. H. Smith
 76. Mr. J. H. Smith
 77. Mr. J. H. Smith
 78. Mr. J. H. Smith
 79. Mr. J. H. Smith
 80. Mr. J. H. Smith
 81. Mr. J. H. Smith
 82. Mr. J. H. Smith
 83. Mr. J. H. Smith
 84. Mr. J. H. Smith
 85. Mr. J. H. Smith
 86. Mr. J. H. Smith
 87. Mr. J. H. Smith
 88. Mr. J. H. Smith
 89. Mr. J. H. Smith
 90. Mr. J. H. Smith
 91. Mr. J. H. Smith
 92. Mr. J. H. Smith
 93. Mr. J. H. Smith
 94. Mr. J. H. Smith
 95. Mr. J. H. Smith
 96. Mr. J. H. Smith
 97. Mr. J. H. Smith
 98. Mr. J. H. Smith
 99. Mr. J. H. Smith
 100. Mr. J. H. Smith

35 In many cases the optically active substrate
selected in conjunction with a specific optical detector
is not readily reactive nor will it retain the nucleic

acid probe. Thus, the surface must be modified with a material which enhances or assists in the immobilization of the probe onto the optical substrate. These materials are referred to as attachment layers. The materials
5 selected for the attachment layer must provide the following characteristics.

Attachment layers must react either in a covalent or very strong non-covalent manner with the optical substrate. The probe may be adhered to the attachment
10 layer either covalently or passively. The attachment layer may be activated to react with the probe, the probe may be activated to react with the attachment layer, or both may be chemically activated to react with each other. The attachment layer can be selected to determine the type
15 of interaction (hydrophobic, hydrophilic, ionic, hydrogen bonded) which occurs between itself and the capture probe. Attachment layers may be applied to the surface of the optical substrate by spin coating, solution coating, vapor deposition, spray coating or the like. The layer must be
20 applied in a uniform fashion from a solvent system which will not damage the optical substrate or the chemical properties of the attachment layer. Ideally, the solvent will volatilize from the surface film during the final curing process.

25 In a preferred embodiment the invention features a device with an amplifying probe reagent able to bind to the target nucleic acid and create an increase in mass change on the optically active layer, without disrupting the thin film effect, when the target nucleic acid is
30 bound to the target specific capture probe.

An "amplifying probe reagent" is designed to increase the mass of the immobilized target nucleic acid on the optically active substrate. This amplification may be required to increase the sensitivity of the hybridiza-
35 tion assay in the optical thin film detection system. The amplifying probes are attached to another catalytic component or particle which will increase the mass when the

0002559-101001

target nucleic acid is captured on the surface. The only requirement for such a material is that it can be tightly associated with the amplifying probe and that the resulting mass deposited at the surface not disrupt the thin film effect. When a catalytic component is attached to the signal amplifying probe, or amplifying probe, it may act on yet another material, further increasing mass on the optical substrate. There may be a surface immobilized capture probe and one or more signal amplifying probes.

By "increase in mass" is meant that the mass change produced is greater than that produced by the binding of the target nucleic acid.

By "without disrupting the thin film effect" is meant that the optical effect generated by light impinging on the optically active substrate is not destroyed by the introduction of additional materials to the surface of the substrate. For example, materials which would scatter light are disruptive to a thin film interference or other reflective techniques, as they would artificially reduce the signal available to a detector.

In further preferred embodiments the amplifying probe reagent comprises a target specific nucleic acid sequence and a catalytic component or a particle; the catalytic component is capable of interacting with additional materials to increase the mass change and result in a second set reflective and transmissive properties without disrupting the thin film effect; the catalytic component is an enzyme; and the particle is selected from the group consisting of metallic particles, silica particles, and film forming latexes.

By "catalytic component" is meant any material which can interact with a substrate to create an insoluble product. Examples of these materials include enzymes, metals and other components which cause a reaction to occur faster than it would occur in the absence of that material.

By "particle" is meant a material such as a film forming latex or small non-scattering metal or glass particles.

By "additional materials" is meant an assay component which is specifically modified by the catalytic component to produce a precipitating material. The precipitating agent may be a substrate for an enzyme, e.g., containing 3,3',5,5'-tetramethylbenzidine when the enzyme conjugate has an immobilized peroxidase or the precipitating agent is a substrate containing 5-bromo-4-chloro-3-indolyl phosphate when the conjugate is alkaline phosphatase.

The following preferred embodiments are applicable to the device with and without the use of an amplifying probe reagent. The attachment layer is selected from the group consisting of polymeric siloxanes, mixtures of polymeric siloxanes, film forming latexes, and silyl modified nucleotides.

The optically active substrate is selected from the group consisting of silicon, glass, amorphous silicon, plastic, metals, amorphous silicon on glass, amorphous silicon on plastic, and composites of these materials.

An anti-reflective film may be provided between the optically active substrate and the attachment layer. This film which may be formed from silicon nitride, silicon oxides, titanium dioxide, silicon oxynitride or cadmium sulfide and the like. This film acts to cause incident light to undergo interference such that a specific color is produced on the surface of the substrate. This film interacts with other layers on the substrate to ensure that a color change or wavelength intensity change is observed when the target nucleic acid is present on the device.

In a preferred embodiment the anti-reflective film is selected from the group consisting of silicon nitride, composites of silicon and silicon oxides, ti

1941	1942	1943	1944	1945	1946	1947	1948	1949	1950	1951	1952	1953	1954	1955	1956	1957	1958	1959	1960	1961	1962	1963	1964	1965	1966	1967	1968	1969	1970	1971	1972	1973	1974	1975	1976	1977	1978	1979	1980	1981	1982	1983	1984	1985	1986	1987	1988	1989	1990	1991	1992	1993	1994	1995	1996	1997	1998	1999	2000	2001	2002	2003	2004	2005	2006	2007	2008	2009	2010	2011	2012	2013	2014	2015	2016	2017	2018	2019	2020	2021	2022	2023	2024	2025	2026	2027	2028	2029	2030	2031	2032	2033	2034	2035	2036	2037	2038	2039	2040	2041	2042	2043	2044	2045	2046	2047	2048	2049	2050	2051	2052	2053	2054	2055	2056	2057	2058	2059	2060	2061	2062	2063	2064	2065	2066	2067	2068	2069	2070	2071	2072	2073	2074	2075	2076	2077	2078	2079	2080	2081	2082	2083	2084	2085	2086	2087	2088	2089	2090	2091	2092	2093	2094	2095	2096	2097	2098	2099	2100	2101	2102	2103	2104	2105	2106	2107	2108	2109	2110	2111	2112	2113	2114	2115	2116	2117	2118	2119	2120	2121	2122	2123	2124	2125	2126	2127	2128	2129	2130	2131	2132	2133	2134	2135	2136	2137	2138	2139	2140	2141	2142	2143	2144	2145	2146	2147	2148	2149	2150	2151	2152	2153	2154	2155	2156	2157	2158	2159	2160	2161	2162	2163	2164	2165	2166	2167	2168	2169	2170	2171	2172	2173	2174	2175	2176	2177	2178	2179	2180	2181	2182	2183	2184	2185	2186	2187	2188	2189	2190	2191	2192	2193	2194	2195	2196	2197	2198	2199	2200	2201	2202	2203	2204	2205	2206	2207	2208	2209	2210	2211	2212	2213	2214	2215	2216	2217	2218	2219	2220	2221	2222	2223	2224	2225	2226	2227	2228	2229	2230	2231	2232	2233	2234	2235	2236	2237	2238	2239	2240	2241	2242	2243	2244	2245	2246	2247	2248	2249	2250	2251	2252	2253	2254	2255	2256	2257	2258	2259	2260	2261	2262	2263	2264	2265	2266	2267	2268	2269	2270	2271	2272	2273	2274	2275	2276	2277	2278	2279	2280	2281	2282	2283	2284	2285	2286	2287	2288	2289	2290	2291	2292	2293	2294	2295	2296	2297	2298	2299	2300	2301	2302	2303	2304	2305	2306	2307	2308	2309	2310	2311	2312	2313	2314	2315	2316	2317	2318	2319	2320	2321	2322	2323	2324	2325	2326	2327	2328	2329	2330	2331	2332	2333	2334	2335	2336	2337	2338	2339	2340	2341	2342	2343	2344	2345	2346	2347	2348	2349</
------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	------	--------

By "degree of rotation observed in polarized light" is meant the attenuation of the degree or amount of rotation measured in polarized light incident upon the optically active substrate before and after reaction with

the target molecule as measured by a change in intensity of the incident light.

By "changes in ellipticity of the impinging polarized light" is meant the attenuation of the ellipticity measured in polarized light incident upon the optically active substrate before and after reaction with the target molecule as measured by a change in intensity of the incident light.

In additional preferred embodiments the target nucleic acid is DNA, rRNA, mRNA, tRNA, small nuclear RNA, or complexes of said nucleic acid with other materials; the target nucleic acid is single stranded or double stranded; the target nucleic acid is obtained from a bacterium, a virus, a human cell, a culture, serum, plasma, blood, urine, sputum, tissue sample, or other biological fluid. Target nucleic acid is obtained from a source by the use of routine extraction and isolation procedures familiar to those who practice the art. The target nucleic acid may also require denaturation to allow for hybridization with the capture probe, such procedures are also standard in the art.

In a further preferred embodiment, the capture probe is a synthetic or biologically produced nucleic acid which may consist of DNA, RNA, or a chimera; the capture probe is a linear strand providing single or multiple copies of a sequence complimentary to the target nucleic acid; the capture probe is a branched, multi-copy sequence complimentary to the target nucleic acid; the capture probe is adhered to the attachment layer by hydrophobic interactions; the capture probe is adhered to the attachment layer by hydrophilic interactions; the capture probe is adhered to the attachment layer by ionic interactions; the capture probe is adhered to the attachment layer by hydrogen bonding; the attachment layer comprises a film forming latex and the capture probe is a chimeric probe which is covalently attached to the attachment layer.

By "chimera" is meant that the capture probe consists of both DNA and RNA. For example, a single ribonucleotide maybe incorporated into a DNA capture probe and is used in covalent attachment of the capture probe to the optically active surface. The ribonucleotide residue may be treated with an oxidizing agent such as periodate to produce a dialdehyde which is reactive with a carbonyl hydrazide modified surface. A covalent modification of the optically active substrate is produced.

By "branched multi-copy sequence" is meant a probe with a branch point such that from emanating branches a copy of the specific capture sequence is extended, thus presenting multiple copies of the capture probe.

In a second embodiment the invention features a method for detecting the presence or amount of a target nucleic acid. The method consists of: preparing a sample, potentially containing a target nucleic acid, for hybridization, contacting the sample with a capture probe supported on an optically active substrate under conditions such that the probe specifically hybridizes to the target, and determining the amount or presence of the target on the optically active substrate by an optical thin film detection method.

By "preparing a sample" is meant treatment of a sample so that a target nucleic acid is in a condition that would allow for hybridization with a capture probe and includes extraction and isolation procedures known to those skilled in the art.

In a preferred embodiment the target nucleic acid after being bound to the capture probe is contacted with an amplifying probe reagent.

In a third embodiment, the invention features a method for increasing capture probe density whereby the probe is applied to an attachment layer on an optically active substrate by spin coating. The density of the

immobilized probe is increased by this process relative to a conventional solution coating process.

By "capture probe density" is meant the amount of capture probe available to bind the target nucleic acid or the number of capture probes per specific amount of surface area.

By "spin coating" is meant the standard semiconductor coating procedure.

In a fourth aspect, the invention features a kit for an optical assay for a target nucleic acid having a test device with an optically active substrate with an attached capture probe which is reactive with the target nucleic acid, and a reagent adapted to react with the target bound to the surface to alter the mass on the surface. Preferably, the reagent is an enzyme conjugate or a polymeric film forming latex.

The kit comprises an optically active substrate coated with a target specific capture probe. The kit may contain reagents for the extraction of the target oligonucleotide from a biological sample, reagents to destabilize the initial target duplex or other secondary structure, hybridization reagents, stringency washes, sample processing tubes and transfer pipettes, and amplifying reagents if required.

In a fifth embodiment the invention features an optical assay device for detecting the presence or amount of a target nucleic acid comprising: an optically active substrate exhibiting a first set of reflective properties in response to light impinging thereon, and exhibiting a second set of reflective properties different from the first set, in response to the light when the target nucleic acid is bound to a target specific capture probe so as to result in a mass change on the optically active substrate. The target specific capture probe attached to said optically active substrate, and detection of said second set of reflective properties indicates the presence or amount of said target nucleic acid.

Other features and advantages of the invention will be apparent from the following description of the preferred embodiments thereof, and from the claims.

BRIEF DESCRIPTION OF THE FIGURES

5 Figure 1 is a chart comparing the amount of HRP/TMB precipitation on various attachment surfaces coated with biotinylated DNA. Solid rectangles represent DNA and conjugate. Darkly stippled rectangles represent
10 conjugate only. Lightly stippled rectangles represent DNA only. Striped rectangles represent no DNA and no conjugate. The y axis represents thickness in angstroms normalized to the substrate thickness. The x axis represents the various attachment chemistries.

15 Figure 2 is a chart comparing the thickness of alkaline phosphatase reaction product on a T-polymer surface with the hybridization concentration of M13mp18 DNA. Solid rectangles represent DNA and conjugate. Darkly stippled rectangles represent conjugate only.
20 Lightly stippled rectangles represent DNA only. Striped rectangles represent no DNA and no conjugate. The y axis represents thickness in angstroms normalized to the substrate thickness. The x axis represents concentrations of M13mp18 DNA in the initial hybridization reaction.

25 Figure 3 is a chart comparing the absorbance of substrate at 410 nm with the composition of spin coating solutions of biotinylated DNA coated onto T-polymer surfaces which were subjected to various post coating treatments. Solid rectangles represent no salt in the coating
30 solution. Darkly stippled rectangles represent medium salt concentration in the coating solution. Lightly stippled rectangles represent high salt concentration in the coating solution. The y axis represents absorbance at 410 nm. The x axis represents post coating treatment:
35 incubation times and temperatures.

Figure 4 is a chart comparing the amount of capture probe remaining bound under various stringency

00000000-101001

conditions. Capture probe was initially covalently bound (solid rectangles); adsorbed (stippled rectangles) or represent non-covalently bound (striped rectangles). The y axis represents absorbance at 450 nm. The x axis represents time of incubation at 68°C in water.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

The following descriptions are for further illustrating the various embodiments of the present invention and are in not intended to be limiting in scope.

The first component required is the optically active substrate. The substrate may be intrinsically optically active or modified to provide the appropriate properties for the detection method selected. Detection methods described include a visual interference assay and numerous instrumented systems including ellipsometry-comparison, null, photometric and other modifications, attenuation of polarized light at non-Brewster angles, profilometry, scanning tunneling microscopy, surface plasmon resonance, evanescent wave techniques, or atomic force microscopy.

This invention is suited to use of a variety of optically active substrate materials and formats based on the needs of the end user. The optically active substrate can be formed of, or have coated on it, a material that provides either diffuse or specular reflection, it may be rigid or flexible, reflective or transmissive. Devices designed for instrumented analysis do not require an anti-reflective (optical thin film) coating on the substrate, while those designed for viewing by eye require such a coating. Criteria useful for selecting an optical substrate for instrumented applications, or for viewing by eye of a color-signal generating application, are presented below.

A wide range of rigid materials may form the optically active substrate, including glass, silicon, fused silica, plastic, ceramic, metal, and semiconductor

materials. The substrate may be of any thickness desired. Flexible optical substrates include thin sheets of plastic and like materials. Most substrates require only a standard solvent, plasma etching, or acid cleaning, well known to those skilled in the art, before subsequent layers may be deposited on them.

The surfaces of many solid materials, such as glass, and semiconductor materials, such as silicon, metals, etc., are sufficiently smooth to provide specular reflection if they are polished. For use in a reflection-based assay the major requirement in selecting an optical substrate is that the reflection occur, or be made to occur, only at the upper surface. This is especially critical for devices which include an interference film which are viewed by eye. This is accomplished by vapor deposition of a thin metal film on the substrate, and attachment of subsequent optical layers by techniques known to those skilled in the art. For example, the uppermost surface of a glass substrate may be coated with a layer (amorphous silicon) to prevent unwanted reflections from the lower surface.

If the substrate is to be used in a reflection mode, and is partially or fully transparent, it may be coated with an opaque material to block transmitted light and allow reflection to occur only from the upper surface. For example, a glass substrate may be coated with a layer of aluminum, chromium, or other transparent conducting oxide, by mounting in a vacuum chamber facing an aluminum-filled tungsten boat. The chamber is evacuated to a pressure of 1×10^{-5} Torr. Current is passed through the tungsten boat, raising it to a temperature at which the aluminum deposits on the substrate at a rate of $20\text{\AA}/\text{second}$ for 100 seconds, coating the glass with an opaque layer of aluminum having a thickness of 2000\AA . Thinner layers of aluminum or chromium may also be used to eliminate any back surface reflections. Non-conducting deposition techniques may be used to deposit the metal film.

The aluminum-coated glass, described above, may be considered optically passive. Thus, if it is coated with a layer of hydrogenated amorphous silicon (a-Si:H), the optical characteristics of the substrate will be derived from the a-Si:H alone. The aluminum-coated glass is required only when the amorphous silicon deposition process requires a conducting surface. Techniques which do not require the use of a conducting surface for the deposition of amorphous silicon are known. To produce this substrate, the aluminum-coated glass is mounted on one of two opposing electrodes in plasma-enhanced chemical vapor deposition system. The system is evacuated, and the substrates are heated to 250°C. A constant flow of silane (SiH₄) gas into the chamber raises the pressure to 0.5 Torr. A plasma is struck by applying 10 mW/cm² of RF power to the electrodes. A film of a-Si:H deposits on the substrates, and grows to a thickness of approximately 1000 nm in about 75 minutes. The a-Si:H so formed may form the first optically functional layer on the test surface.

A glass substrate coated only with a-Si:H (without the aluminum layer) is also useful in this invention. Transparent substrates, such as glass, fused silica, sapphire, and many plastics may be used in instrument transmission measurements, without additional modification. Color-signal generation visible to the eye is possible with a transmissive substrate where the anti-reflection properties of the coatings are determined from the transmitted light.

In one example, the optical substrate is formed from a silicon crystal which is grown and extruded to 4 inches in diameter and then diamond sawed to form a wafer. The wafers are treated with chemical etchants to smooth the surface and reduce flaws. The wafers are lapped or ground with aluminum oxide, titanium oxide, or silicon carbide particles in a talc slurry. The initial grain size is large and successively smaller particle sizes are used to produce an increasingly smoother surface. Both

sides of the wafer are subjected to this process. The final lapping process leaves a very diffusely reflective surface. Wafers may be further processed with chemical or plasma etching to modify the diffuse reflecting characteristic of the substrate. Once the wafers are lapped, they are cleaned using the following process or a known modification thereof: the wafers are sonically cleaned with a cationic detergent, followed by a rinse with 18 megaohm water. Then they are cleaned with an anionic detergent, followed by a rinse in 18 megaohm water. They are ultrasonically cleaned with an aqueous ammonia solution made of 370 ml of 30% H_2O_2 , 250 ml of aqueous ammonia and 9 gallons of water, and are rinsed in a cascade of water with the final rinse being with 0.1 micron filtered water. They are then spin-dried and are ready for optical coating. An alternative to this procedure is the "RCA Clean" described in *Polymer Surfaces and Interfaces*, edited by W.J. Feast and H.S. Munro, John Wiley and Sons, N.Y., N.Y., page 212, 1987.

The substrate material may be cut, sawed, scribed, laser scribed, or otherwise manipulated into the desired test piece configuration. Suitable test pieces for a single use assay are 0.5 cm² to 1 cm² with 0.75 cm² being preferred. Test piece sizes are not restricted to the above, as alternative formats may require substantially more or less reactive test surface.

For the color-signal generation methods only, substrate selection will determine the characteristics of the anti-reflective material or materials used in subsequent coating steps. The simplest description of a single optical thin film is that the substrate is coated with a thin layer of material such that reflections from the outer surface of the film and the outer surface of the substrate cancel each other by destructive interference. Two requirements exist for exact cancellation of reflected light waves. First, the reflections must be 180° out of

phase and, second, they must be of equal amplitude or intensity.

In the reflection mode, the optical thin film properties of the coatings of a device of this invention
5 suppress the reflection of some wavelengths of light and enhance the reflection of others. This causes the suppressed wavelengths of incident light to enter the substrate, or an opaque coating on the substrate where they are absorbed. Most of the light of other wavelengths,
10 whose reflection is not suppressed, does not enter the coated substrate and is reflected, however, some components may be absorbed. As the optical thickness of the coating changes, the range of wavelengths in the reflected light changes. In transmission mode, the properties of
15 the coatings suppress the reflection of some wavelengths of light and enhance the reflection of others, as in the reflection mode. This causes the suppressed wavelengths of the incident light to enter the substrate and to be transmitted. Light of other wavelengths, whose reflection
20 is not suppressed to as great an extent is reflected, and transmitted to a lesser extent. As the optical thickness of the coating changes, the range of wavelengths in the transmitted light changes.

Where visible signal generation is required,
25 the final assay result may also be measured by instrumentation. Ideally, for the production of a perfect interference film using only the a nucleic acid probe, and an optical substrate, the substrate should have an approximate refractive index of the square of the refractive
30 index of the receptor layer (see below), i.e., $(1.5)^2$ or 2.25 (variations in this number can still provide useful devices of this invention). The material selected should be mechanically stable to subsequent processes, reflective, and of known refractive index. It is not always
35 possible to match the optical substrate to a particular film, for example, a biological film. In these cases, an intermediate optical thin film must be used to compensate

for the lack of a suitable optical substrate. For eye-visible color-signal generation, the substrate material is subject to two restrictions: first, it must adhere to the optical thin film material, and second, in the simplest case, the refractive index of the substrate should approximately equal the square of the refractive index of the material directly above it or, on a more complex test surface, the refractive index of the substrate should be selected to fit generally one of the formulae in Table 3, pp 8-48 to 8-49, of the "Handbook of Optics". For example, use of a silicon wafer with a refractive index of approximately 4.1 allows a test surface to be designed with a wide variety of corresponding optical thin films or anti-reflective materials. The material should be coated to a thickness of a quarterwave for the wavelengths to be attenuated, or variations in the formulae. Those skilled in the art will realize that various other substrate materials are equally suited for use as a test surface if they satisfy the above criteria.

The optical thin film coating is deposited onto the surface of the substrate by known coating techniques; for example, by sputtering or by vapor phase deposition in a vacuum chamber. Various other useful coating techniques are known to those skilled in the art. Materials useful as optical thin film coatings are formed of clear material which is significantly transmissive at the thickness utilized, and suppresses some wavelength of reflective light when coated onto the substrate. The film, once deposited onto the optical substrate, is also stable to subsequent processes.

Preferably this test surface will have fewer optical layers, but more complex test surfaces possessing more layers corresponding to the known formulae. As already noted, the theoretical calculations are the starting point for material selection. Theoretical considerations may be used to determine which materials are compatible with a pre-selected substrate. The coating

[illegible]

20 A method for selection of the optimal thick-
nesses of each layer for a device of the present invention
is disclosed for a silicon nitride film on silicon. In
step 1, a silicon substrate is provided either with a
specular or non-specular surface. A silicon nitride film
25 is provided on this surface in steps 2 and in step 3, this
film is eroded away in a stepwise fashion by heating and
stirring in an appropriate solution. The timing of each
step is selected such that the portion which is subjected
to erosion for the longest period of time exhibits a pale
30 gold color, while that portion which is not exposed to
erosion exhibits a deep blue color. In steps 5 and 6
respectively, an attachment layer and a receptive material
layer for the target nucleic acid to be detected are pro-
vided on the silicon nitride. These layers are provided
35 in a thickness which may be determined empirically, or can
be similarly optimized (e.g., in this stepwise fashion) if
so desired. In step 7, an assay is performed with three

portions of the strip being treated in a different manner such that a negative response, a weak response, and a strong response can be recorded. The thickness of silicon nitride useful in the invention can be determined by those
5 sections providing the strongest weak positive response in the test while maintaining a clean negative response.

Specifically, a silicon wafer was prepared with a thick coating (800Å) of silicon nitride so that the wafer appeared to be a deep blue. Then the optical thin
10 film material was etched off the wafer in a hot, phosphoric acid bath to produce a wedge of interference colors. The optical material was etched such that 300Å remained at one end of the wedge and 700Å remained at the other end of the wedge. (At 180°C the silicon nitride was
15 removed at approximately 20Å per minute.) The optimal film thickness is most readily selected based on the composite test surface analysis. This process maximizes the visual contrast obtained for the specific assay under development.

20 Silicon nitride is easily etched to produce the wedge of thicknesses needed for this empirical evaluation. Many materials are susceptible to an acid or base etching processes. Other chemical methods of etching materials are known. If a desired optical film is not easily
25 removed from a particular optical substrate because the film is too easily destroyed, or the optical substrate is not stable to the required etchant, another method of generating the wedge may be used. For instance, monocrystalline silicon is not stable to prolonged exposure to
30 basic solutions. If an optical film on silicon requires a basic etchant the wedge can not be generated using a chemical approach.

Several alternatives exist; first, the optical film may be deposited on an optical substrate which is
35 introduced stepwise into the coating chamber over a period of time. Each newly exposed section will receive a thinner coating than the previously exposed section. Second,

the substrate may be masked and the mask removed stepwise over a period of time. Third, several different coating runs each producing a different thickness of optical material may be performed. Fourth, ion milling may also
5 be used to etch certain materials. For any given optical substrate and substitute optical thin film, of the same refractive index as the original optimized optical thin film, the process need not be repeated. Minor thickness adjustments may be required if the refractive index is not
10 exactly that of the original material.

Thus, the formulae established for the coating of optical thin films are used as a guideline only for the production of a test surface suited to a specific binding assay. For a pre-selected substrate, the square root
15 dependence of an optical thin film is used to screen appropriate optical materials. Some deviation from the perfect square root dependence is acceptable for this invention. The use of a quarterwave thickness of the optical coating is only an initial guide to coating thick-
20 ness. Thickness of the optical thin film must thus be empirically derived in consideration of the nucleic acid capture probe. The composite of the nucleic acid capture probe and the optical thin film of this invention does not meet the conditions theoretically required to produce such
25 a film. Neither the thickness nor the refractive index rules are followed. Surprisingly such deviation from these accepted formulae results in a test surface which is very sensitive to mass changes or thickness changes.

While of less importance, the relative thick-
30 nesses of each layer, and not just the optical thin film layer, may be varied as described above to optimize the final test device for any particular attachment layer and receptive material layer.

Other optical thin film materials that have a
35 similar refractive index include, but are not limited to: tin oxide, zinc oxide, chromium oxide, barium titanate, cadmium sulfide, manganese oxide, lead sulfide, zinc

Patent 210/215

[illegible]

An attachment layer must be stable under the conditions used to attach the capture probe to the surface and to subsequent washes. The methods of applying a variety of attachment layers to an optical substrate are provided in the examples below. The composition of the attachment layer will determine the mode of immobilization for the capture probe.

Ideally, the surface activation technique should provide a covalent modification of the surface for sta-

1. 1990年12月，中共中央、国务院作出《关于实行“八七”扶贫攻坚计划，进一步减少贫困人口的通知》，要求到1995年基本解决农村贫困人口温饱问题，使贫困人口人均年纯收入达到200元以上。

The capture probe could also be synthesized containing a Psoralen C2 Phosphoramidite which was originally designed to introduce a fluorescent label into a nucleic acid probe. This molecule when photoactivated will cross-link to any available thymine. The psoralen

modification would be used to attach the capture probe to the surface. It may be desirable to add a linker between the probe and the Psoralen monomer. It is also important that the probe not contain a TT sequence or they will dimerize upon photoactivation. Probes can be designed with branching spacers using phosphoramidite chemistries including 5'-Branched modifier C3 or C7 and 3' Amino-modifier C3CPG to introduce multiple copies of probe to linkers with single points of attachment. A primary amine modified spacer could be incorporated into the capture probe which could then be reacted with an aldehyde coated surface. Imine formation can be promoted by NHS/carbodiimide chemistries and then may be reduced with NaBH₄. If the oxygen in the phosphate groups of the DNA backbone is replaced with a sulfur group, then coordination complexes with metal surfaces can be used to immobilize the probe.

One of the best approaches for the generation of a long oligonucleotide on the surface is to immobilize an oligonucleotide on the surface then ligate the remaining sequence onto the surface using a ligase reaction. This could be used to covalently attach a probe which contains a large number of repeats of the desired sequence. This would increase the efficiency of the capture of the target by improving the steric availability of the probe for hybridization.

A hydrophobic surface may be used to immobilize a capture probe which is modified with a poly T tail. A poly T tail is very hydrophobic and can be used to associate with the surface and drive the attachment of the probe to the surface. When this approach is used, samples should be treated to remove poly A tails which would associate with the surface and block the desired hybridization reaction. Alternatively a poly T probe could be used to isolate an mRNA and then specifically identify the mRNA through an amplifying probe.

A carbonyl hydrazide surface may be generated by applying a thin film of a carboxylate modified polymer (such as a film forming latex) to the surface by aerosol, spin coating, dip coating, etc. The carboxylate is then
5 treated with N-hydroxysuccinimide and a carbodiimide followed by hydrazine to create the hydrazide surface. It is also possible to use an amine modified surface for direct interaction with the aldehyde groups.

A capture probe may be modified with a free
10 thiol group at the 3' or 5' end. This free thiol may be reacted with a surface thiol to form a disulfide bond and thus link the probe to the surface. A mercapto siloxane may be used to introduce the thiol onto the surface through a spin coating process. Or a polymer may be
15 combined with a siloxane such as the T-Polymer to create a hydrophobic surface which helps draw the probe to the surface prior to actual attachment. In this case unreacted surface thiols must be blocked prior to subsequent processing, and conditions for the assay must not reduce
20 the dithiol to free thiol groups.

A capture probe may also be linked to a material which is easily adhered non-covalently to the surface. When a surface is coated with the T-polymer, proteins strongly adhere to the solid support. The oligonucleotide
25 is modified at the 5' end with hexanolamine which can be added directly to the probe by a nucleic acid synthesizer. A maleimide is synthesized by the addition of 3-maleimidobenzoic acid in basic solution and purification by anion exchange chromatography. This modified capture
30 probe is then incubated with the protein either in solution or coated onto a solid support to couple the probe and protein. The ratio of the probe: protein and other parameters can be set to control the level of probe incorporation and thus the surface density obtained.

35 The capture probe must be tightly associated with the surface so as to minimize the rate of removal, especially during the final stringency wash processes.

In some cases a signal amplifying probe or probes may be required to achieve the sensitivity desired for the detection of the target nucleic acid. As with the capture or immobilized probe, the amplifying probe may be a DNA or RNA probe. The amplifying probe may be modified to include additional mass generating materials. And the

oligonucleotide reporter sequence selected should be well separated from the sequence hybridized by the capture probe.

One possible method of signal amplification is to attach the amplifying probe to horseradish peroxidase (HRP) or alkaline phosphatase (AP) and use in combination with a precipitating substrate. See Renz, M., and Kurz, K., "A Colorimetric Method For DNA Hybridization", Nuc. Acids Res., 12, 3435-3444, 1984 for a method to couple an oligonucleotide to these enzymes. Catalytic, but non-enzymatic, reactions which have a specific catalyst and reactant and lead to the formation of an insoluble product may also be utilized. Some mechanism must exist which will allow the attachment of the amplifying probe to the catalyst.

Signal amplification reagents can be attached to the nucleic acids by a variety of linking agents including glutaraldehyde, N,N'-o-phenylenedimaleimide, N,N'-oxydimethylenedimaleimide, N-succinimidyl-4-(N-maleimidomethyl)cyclohexane-1-carboxylate, N-succinimidyl-maleimidobenzoate, and N-succinimidyl-3-(2-pyridyldithio)propionate. Signal amplification reagents can include enzymes, metal particles, latex particles, multiple copies of an enzyme or multiple enzymes, highly branched nucleic acids or other similar compounds which can be specifically attached to a secondary probe. These reagents should be selected to specifically enhance the mass of the immobilized target while not disrupting the thin film effect. While the packing of the molecules in the layer do not approach a true thin film, due to the percent occupancy of all available binding sites, they must not disrupt the thin film effect in order to maximize the quality of the generated signal. Thus, amplification

1. 1990年1月1日至1990年12月31日止，共发生10起，其中：1990年1月1日至1990年6月30日止，共发生5起；1990年7月1日至1990年12月31日止，共发生5起。
2. 1991年1月1日至1991年12月31日止，共发生10起，其中：1991年1月1日至1991年6月30日止，共发生5起；1991年7月1日至1991年12月31日止，共发生5起。
3. 1992年1月1日至1992年12月31日止，共发生10起，其中：1992年1月1日至1992年6月30日止，共发生5起；1992年7月1日至1992年12月31日止，共发生5起。
4. 1993年1月1日至1993年12月31日止，共发生10起，其中：1993年1月1日至1993年6月30日止，共发生5起；1993年7月1日至1993年12月31日止，共发生5起。
5. 1994年1月1日至1994年12月31日止，共发生10起，其中：1994年1月1日至1994年6月30日止，共发生5起；1994年7月1日至1994年12月31日止，共发生5起。
6. 1995年1月1日至1995年12月31日止，共发生10起，其中：1995年1月1日至1995年6月30日止，共发生5起；1995年7月1日至1995年12月31日止，共发生5起。
7. 1996年1月1日至1996年12月31日止，共发生10起，其中：1996年1月1日至1996年6月30日止，共发生5起；1996年7月1日至1996年12月31日止，共发生5起。
8. 1997年1月1日至1997年12月31日止，共发生10起，其中：1997年1月1日至1997年6月30日止，共发生5起；1997年7月1日至1997年12月31日止，共发生5起。
9. 1998年1月1日至1998年12月31日止，共发生10起，其中：1998年1月1日至1998年6月30日止，共发生5起；1998年7月1日至1998年12月31日止，共发生5起。
10. 1999年1月1日至1999年12月31日止，共发生10起，其中：1999年1月1日至1999年6月30日止，共发生5起；1999年7月1日至1999年12月31日止，共发生5起。

For the analysis of specific binding reactions
20 on a test surface, a number of modifications greatly
improve the performance of the Comparison Ellipsometer.
The original design relied on the observer's eye for
inspection of the surface.

A detector may be mounted where the eyepiece is located in the original instrument. It may also be mounted at 90° to the side of the light path by incorporation of a partially silvered mirror or beamsplitter set at 45° to reflect a portion of light to a detector, and the rest to the eyepiece for visual alignment of samples. If the mirror is inserted into the optical path, the spot intensity reaching the detector will be only a fraction of the light available. If the detector is directly in the optical pathway without a mirror, 100% of the sample intensity reaches the detector. When a beamsplitter and eyepiece are included in the apparatus, if care is not taken, stray light can be introduced which degrades the optical signal incident on the detector.

A photodiode array may be programmed to dedicate individual photodiodes to measure the intensity of reaction zones or spots, while other photodiode arrays measure the background, or control zones. Simultaneous measurement of the spot intensity and the background intensity allows each reading to be accurately corrected for test surface background.

Either a linear array or a matrix array may be used. A linear array may only measure along one, pre-set axis of the sample spot depending on the size and resolution available in the arrays. The matrix array could measure the entire reacted spot plus background.

The instrument may also be modified to include a variable magnification function or a zoom to allow different spots to fill the photodiode without capturing any background signal. A semi-reflective mirror was introduced between the zoom and the ocular at 45°. Within the ocular, suitably positioned in the middle of the field and in focus was set a reticle of an ellipse. The reticle was selected to match an average sample spot size. On the optical path center line, reflected 90° from the principal axis, was set a mask which matches the size of the reticle. The distance from the center of the mirror to the reticle is the same as from the center of the mirror to the mask. The mirror was mounted by adjusting screws so that the image seen within the reticle would be identical to the image appearing within the mask. Behind the mask, a distance of a few millimeters, was mounted a photosensitive cell arranged to only read the light which passes through the mask and therefore from the selected image. The semi-reflective mirror is of a thickness such that a secondary image appears from the second surface. This is eliminated by using a suitably coated thin mylar membrane as the beamsplitter.

A constant light source, white light or monochromatic, is provided by using a power supply that has feedback capabilities. A photoresistor is mounted inside

1. 姓名	2. 性别	3. 年龄	4. 民族	5. 籍贯	6. 职业	7. 文化程度	8. 婚姻状况	9. 子女情况	10. 宗教信仰	11. 健康状况	12. 其他
张三	男	45	汉族	山东	工人	高中	已婚	2人	无	良好	
李四	女	38	汉族	河南	教师	大学	已婚	1人	无	良好	
王五	男	52	汉族	广东	干部	大学	已婚	2人	无	良好	
赵六	女	41	汉族	四川	医生	大学	已婚	1人	无	良好	
孙七	男	35	汉族	浙江	工程师	大学	已婚	2人	无	良好	
周八	女	48	汉族	湖北	会计	高中	已婚	1人	无	良好	
吴九	男	55	汉族	湖南	农民	小学	已婚	3人	无	良好	
郑十	女	32	汉族	广西	护士	大学	已婚	1人	无	良好	
冯十一	男	43	汉族	福建	商人	高中	已婚	2人	无	良好	
陈十二	女	50	汉族	江西	工人	小学	已婚	1人	无	良好	
林十三	男	37	汉族	山西	教师	大学	已婚	2人	无	良好	
黄十四	女	46	汉族	陕西	医生	高中	已婚	1人	无	良好	
周十五	男	53	汉族	甘肃	干部	大学	已婚	2人	无	良好	
吴十六	女	39	汉族	宁夏	工人	小学	已婚	1人	无	良好	
郑十七	男	44	汉族	青海	商人	高中	已婚	2人	无	良好	
冯十八	女	51	汉族	新疆	教师	大学	已婚	1人	无	良好	
陈十九	男	36	汉族	内蒙古	医生	高中	已婚	2人	无	良好	
林二十	女	47	汉族	吉林	工人	小学	已婚	1人	无	良好	
黄二十一	男	54	汉族	黑龙江	干部	大学	已婚	2人	无	良好	
周二十二	女	33	汉族	辽宁	商人	高中	已婚	1人	无	良好	
吴二十三	男	42	汉族	河北	教师	大学	已婚	2人	无	良好	
郑二十四	女	49	汉族	河南	医生	高中	已婚	1人	无	良好	
冯二十五	男	34	汉族	山东	工人	小学	已婚	2人	无	良好	
陈二十六	女	52	汉族	广东	干部	大学	已婚	1人	无	良好	
林二十七	男	38	汉族	四川	商人	高中	已婚	2人	无	良好	
黄二十八	女	45	汉族	湖北	教师	大学	已婚	1人	无	良好	
周二十九	男	56	汉族	湖南	工人	小学	已婚	2人	无	良好	
吴三十	女	31	汉族	广西	医生	高中	已婚	1人	无	良好	
郑三十一	男	41	汉族	福建	商人	大学	已婚	2人	无	良好	
冯三十二	女	48	汉族	江西	工人	小学	已婚	1人	无	良好	
陈三十三	男	57	汉族	山西	干部	大学	已婚	2人	无	良好	
林三十四	女	35	汉族	陕西	教师	高中	已婚	1人	无	良好	
黄三十五	男	43	汉族	甘肃	医生	大学	已婚	2人	无	良好	
周三十六	女	50	汉族	宁夏	工人	小学	已婚	1人	无	良好	
吴三十七	男	37	汉族	青海	商人	高中	已婚	2人	无	良好	
郑三十八	女	46	汉族	新疆	教师	大学	已婚	1人	无	良好	
冯三十九	男	53	汉族	内蒙古	医生	高中	已婚	2人	无	良好	
陈四十	女	32	汉族	吉林	工人	小学	已婚	1人	无	良好	
林四十一	男	44	汉族	黑龙江	干部	大学	已婚	2人	无	良好	
黄四十二	女	51	汉族	辽宁	商人	高中	已婚	1人	无	良好	
周四十三	男	39	汉族	河北	教师	大学	已婚	2人	无	良好	
吴四十四	女	47	汉族	河南	医生	高中	已婚	1人	无	良好	
郑四十五	男	55	汉族	山东	工人	小学	已婚	2人	无	良好	

The reflectometer is a very simple instrument which allows measurement of a color change or a change in intensity. A standard halogen light source is used. This will provide polychromatic light. The light source is positioned relative to the test surface such that the maximum intensity of the incident light impinges the test surface. The detector may be a photomultiplier or the like. The angle with which the light impinges the test surface determines the angle at which the detector is placed relative to that surface.

Another useful instrument is a thin film analyzer which uses a monochromatic light source. If the light is not sufficiently linearly polarized, then a polarizer near the source may be used to polarize the light. The polarizer must be positioned to allow the maximum intensity of light to pass through to the test surface. By off-setting the initial polarizer a component of light polarized perpendicular to the plane of incidence, in addition to the light polarized parallel to

the plane, is allowed to interact with the surface. Light impinges the test surface at an angle which is sufficiently removed from Brewster's angle, between 50 and 75 degrees off the normal. The polarizer/detector is set at the same angle from the normal as the incident light source relative to the test surface. The polarizer is set from 2° to 15° above the setting which aligns the polarizers for total extinction of light. Incident angles of 30° to 40° off the normal provide adequate resolution of very dilute samples, but may not provide sufficient range for all applications. The second polarizer, or analyzer polarizer, cannot adequately minimize the background signal when the light is incident on the surface at angles greater than 65°. However, the dynamic range is sufficient to allow for electronic reduction in the background signal. The light is reflected from the test surface through the polarizer/analyzer combination prior to being measured at the detector. The detector may be a single photodiode or a photodiode array. A blank test surface is placed in the sample position and used to align the second polarizer. The second polarizer should be positioned at an angle with respect to the first polarizer such that it is a few degrees off the minimum (maximum extinction of light through to the detector). Thus, the background of the test surface produces a low detectable signal, but the change in light intensity is now a function of the change in thickness.

The thin analyzer eliminates the reference surface requirements of the previous instrument and is easier to reduce in size. The comparison based instruments require that a specific reference surface be designed for each type of test surface to be used. This limits the range of optical substrates and optical thin films which are compatible with a given instrument, unless means for changing the reference surface is provided. This new instrument easily accommodates any combination of thin film and optical substrate using a simple adjustment

of the analyzer. The instrument may provide better thickness resolution. This instrument and the modified Comparison Ellipsometer may be powered with a 9V battery or other rechargeable power supply. This prototype supplies an increase in numerical aperture, image brightness and focus. This allows a much higher level of magnification to be used which is important for work with smaller spot sizes. Samples may also be applied much closer to one another than is possible with the Comparison Ellipsometer.

EXAMPLES

EXAMPLE 1: Evaluation of Attachment Chemistries

A 5'-biotinylated oligonucleotide (capture probe) was used to evaluate attachment chemistries for the immobilization of DNA capture probes to optically active surfaces. Several attachment or surface chemistries are presented.

20 Surface 1: T-Polymer

A 128 +/- 2 Å layer of T-Polymer-Aminoalkyl T-structure branch point polydimethyl siloxane (Petrarch; Bristol, Pa) was used. A 1:300 (v/v) dilution of the T-Polymer was prepared in 2-methyl-2-butanol. The attachment layer was applied to the silicon wafer by a spin coating method and was cured for 24 hours at 140°C prior to use. For spin coating, a 300 µl sample of this solution was placed on a 100 mm virgin test silicon wafer by micropipette, although automated aerosol or spray delivery systems are equally useful, while the wafer was spinning at 7,000 rpm on a photoresist spin-coater.

Surface 2: R-Polymer

A 70 +/- 2 Å layer of spin on glass was coated onto a virgin silicon wafer as follows. A solution containing 1.6%, each, of trimethyl QAC and octadecyl QAC (quaternary ammonium compound, Petrarch), 36.8% water, 10%

methanol, and 50% isopropanol was prepared. A 400 μ l sample of this solution was applied to the wafer which was attached to a spin coating apparatus and spinning at 3000 rpm. The wafer is spun until a uniform thin film is generated. The glass is then annealed or cured onto the wafer by incubating for 2 hours at 155°C.

Surface 3: Si_xN_y

A 499 +/- 2 Å layer of silicon nitride was applied to the virgin silicon wafer using standard vapor deposition processes known in the semi - conductor industry.

Surface 4: RT II

A 1:1 mixture of the T-Polymer solution with the R-polymer solution was prepared. A 400 μ l sample of this mixture was applied to the wafer which was spinning at 3000 rpm. The wafer was spun until a uniform thin film was generated. The polymer layer is cured onto the wafer by incubating for 2 hours at 155°C.

Sub (B)
DNA capture probe was coated onto these wafer surfaces from a solution containing 50 mM sodium citrate, pH 6.0, 0.1 mg/ml carrier DNA, sheared herring sperm DNA, and 600 μ M biotinylated DNA, 26-mer. The probe sequence was 5'-CGCTAATATCAGAGAGATAACCCAC-3'. Wafers were incubated in this solution overnight at 4°C. Wafers were removed from the solution and washed with 1x phosphate buffered saline containing 0.2% Tween 20™ detergent (PBS/Tween). The wafers were then coated in a BSA (bovine serum albumin) solution for 3 hours at 65°C. The wafers were then rinsed with PBS/Tween detergent.

To measure the amount of biotinylated DNA adsorbed to the surface, the wafers were incubated for 30 minutes with a solution containing streptavidin conjugated to horseradish peroxidase (Immunology Products) was diluted 1:250 in 50 mM MOPS, pH 7.0, containing 3% alkaline treated casein, 0.2% TWEEN20 detergent, and 0.5%

Proclin 300 (an anti-bacterial agent). Wafers were then washed with deionized water and dried under a stream of nitrogen. A drop of TMB precipitating substrate was applied to the surface and the wafers incubated for 30 minutes at room temperature. Thickness increases (in Angstroms) due to substrate deposition were measured using an absolute ellipsometer (Gaertner) which was normalized to the initial substrate thickness. See Figure 1. These experiments were repeated using alkaline phosphatase conjugated to streptavidin and BCIP/nitroblue tetrazolium substrate pair. The R-polymer surface (most polar surface used) and the T-polymer surface (least polar surface used) all performed well. These experiments demonstrate that DNA can be successfully immobilized to the surface of the silicon wafer.

EXAMPLE 2: Sensitivity Evaluation In An Un-optimized Assay

Wafers coated with T-polymer (see Example 1) were coated for 56 hours at 4°C in a solution containing 50 mM sodium citrate buffer, pH 6.0, 5X SSC, and 20 µg/ml of the ssDNA capture probe complimentary to M13mp18. The probe sequence was CGCTAATATCAGAGAGATAACCCAC. Probe coated wafers were removed from coating solution and placed into a blocking solution containing 5X Denhardt's solution, 0.5% SDS, 1 mg/ml carrier DNA, and 25 mM buffer at pH 6.5. They were incubated 16-18 hours at 4°C and then rinsed with phosphate buffered saline containing 0.0005% TWEEN20 detergent at pH 7.4. Capture probe coated wafers were hybridized with M13mp18 plasmid overnight at 60°C in a solution containing 1X Denhardt's solution, 0.5% SDS, 25 mM MES, pH 6.5, 0.2 mg/ml carrier DNA, 5X SSC, a final concentration of M13mp18 was 500 ng/ml, 1 ng/ml or 100 pg/ml. The final hybridization step occurred under the same solution and incubation conditions as the previous step with a final biotinylated amplifying probe concentration of 92 µM. The amplifying probe contains

strand sequence from 6249 to 6273 and was biotinylated at residue 6261. The sequence is GCAGGTCGACTGTAGCAGGATGCCGG. All appropriate controls were performed. Wafers were incubated with a streptavidin alkaline phosphatase conjugate. Precipitating substrate, BCIP/nitroblue tetrazolium, was used to generate an increase in thickness at the surface of the wafer. Thickness increases were measured using an absolute ellipsometer (Gaertner). Results for the experiment are shown in Figure 2. From this experiment, it was concluded that a sensitivity of 1 ng/ml and potentially as low as 100 pg/ml was achieved. This translates to a copy number of roughly 10^{10} for a very un-optimized assay.

15 **EXAMPLE 3: Spin Coating of the DNA Capture Probe**

Spin coating of the DNA capture probe (M13mp18 fragment 6249-6273) was carried out on two wafer polymer preparations: T-polymer and R-polymer. The wafers were prepared as previously described in Example 1. The DNA capture probe was applied using 400 μ l of solution and a speed of 4000 rpm. Three coating solutions were prepared as follows:

High Salt Solution:

25 5 μ l of 10 mg/ml sheared herring sperm DNA
25 μ l of 0.50 M Pipes pH 7.0 buffer
105 μ l of methanol (anhydrous)
315 μ l of biotinylated DNA stock (316 μ g/ml)
50 μ l 20X SSC

Medium Salt Solution:

30 5 μ l of 10 mg/ml sheared herring sperm DNA
25 μ l of 0.50 M Pipes pH 7.0 buffer
105 μ l of methanol (anhydrous)
315 μ l of biotinylated DNA stock (316 μ g/ml)
25 μ l 20X SSC
35 25 μ l H₂O

[illegible]

- After spin coating, the wafers were broken into 6 pieces (chips) and sorted to undergo the following post coating treatments.

- After the post coating treatment process individual 0.75cm^2 test surfaces were cut and placed into assay devices. After the wafers were placed in the device they were washed with wash buffer ($2\times\text{SSC}$, 0.1% (w/v) SDS) to remove any unbound DNA capture probe. A control wafer for each surface was included. The control did not include a conjugate incubation step and received substrate only. Test wafers were incubated for 15 minutes at room temperature with a $100\text{ }\mu\text{l}$ spot of a 1:1000 dilution of a streptavidin/HRP conjugate. The conjugate was aspirated from the surface and then the surface thoroughly washed with wash buffer. A $100\text{ }\mu\text{l}$ spot of the 2 part Kirkegaard and Perry TMB substrate was applied and incubated at room temperature for 10 minutes. The substrate was quantitatively transferred to a microtiter well containing $100\text{ }\mu\text{l}$ of 2.5M sulfuric acid and then the absorbance measured at 410 nm . Results using the T-polymer are shown in Figure 3. Solution coating of the DNA capture probe onto the T-Polymer surface provided a functional surface, but only captured approximately $1/4$ of the probe that the spin coating technique provided. For the solution coating of probe to the surface, the salt concentration of the

coating solution was the most critical variable. The optimal coating solution was determined to be 0.25 mg/ml of carrier DNA, 6X SSC pH 7.5, room temperature incubation, and the best surface was the T-Polymer.

5

EXAMPLE 4: Adherence of Covalently Bound DNA Under Stringent Conditions

Virgin silicon wafers were coated with a layer of film forming latex consisting of free carboxylic acid groups. A 30% stock solution of TC7A (Seradyn, Indianapolis, IN) was diluted to a 0.5% solid in methanol. A 300 microliter sample was applied to the substrate using the spin coating technique and was cured at 37°C for 120 minutes prior to use. A final thickness of this material is preferred to be 240Å. These carboxylic acid groups were reacted with NHS (20 mM), N,N'-dicyclohexylcarbodiimide (DCC, 20 mM) in dioxane. These components were mixed on ice for 15 minutes and then incubated for 4-5 hours at room temperature. Then 32 mmols of hydrazine was added to leave a reactive hydrazide on the surface. The mixture was incubated for 1 hour on ice and then overnight at room temperature. A DNA capture probe with a 3' terminal ribonucleotide residue was treated with sodium periodate at a DNA:NaIO₄ ratio of 1:15 for 1 hour to leave a dialdehyde group on the polynucleotide. The dialdehyde then adds to the carbonyl surface to form a covalent adduct of the capture probe on to the surface.

30 An 18 mer DNA/RNA chimera was utilized as the capture probe. The probe was biotinylated at the 5' end and has a ribonucleotide cytosine on the 3' end. The DNA sequence was 5'-CGAAGCTTGGATCCGCC-3' (ribose). The covalently attached capture probe was treated with S1 nuclease to degrade the entire probe from the surface. 35 The S1 nuclease was mixed in a solution of 0.2 mM NaCl, 0.05 M sodium acetate pH 5.4, 1 mM ZnSO₄, and 0.5% glycerol to a final concentration of 2 units/ml. A section of the

See
B3 7

Sub
B3
Control

wafer was submerged into 7 ml of the enzyme solution and incubated for 10 minutes at 37°C. Wafers were rinsed prior to enzyme treatment in water for 2 hours at 45°C. The enzyme solution was decanted into test tubes and a small volume of water used to rinse the wafers. The combined solution was dried with a SpeedVac system. The pellet was extracted into acetone and the solution dried. These pellets were re-suspended in 70 μ l of water and the A_{260} measured in a microcuvette. The surface density of the probe was determined to be 50 ng/cm². Control surfaces where no NaIO₄ was used, no covalent attachment, did not generate signal. Control surfaces without DNA or without S1 nuclease gave no signal.

Wafers with covalently attached capture DNA probe were incubated at 68°C in pure water for 4, 7, or 24 hours in order to simulate very extreme conditions of stringency. Wafers were removed, dried and incubated with a streptavidin HRP conjugate. Unbound conjugate was rinsed from the surface. The Kirkegaard and Perry two component TMB substrate was applied for 20 minutes at room temperature. After four hours, the intensity of the ELISA was not changed, indicating that the capture DNA probe on the surface had not been stripped to any significant extent. A wafer with adsorbed, non-covalently bound DNA probe was shown to lose all of its DNA probe under these conditions. See Figure 4.

Example 5: Estimated Sensitivity Based On Bound Capture Probe

Sub
B4
30

An 8-mer was synthesized and was 5' biotinylated and had a 3' ribose. The DNA sequence was 5'-AAAGATGTA ribose)-3'. The 8-mer was immobilized using the 15:1 periodate:probe ratio to a TC7 coated optical substrate as described in Example 4. Chips were coated at the concentrations listed in the table below. The amount of immobilized biotinylated DNA was measured by reacting a pre-determined surface area with a sufficient volume of

1:1000 dilution of a streptavidin/horseradish peroxidase conjugate to cover the test surface. The conjugate and surface were incubated at room temperature for 10 minutes. The chips were rinsed 2 times with wash buffer and then water. The Kirkegaard and Perry two component TMB substrate was applied for 20 minutes at room temperature. A volume of the substrate was placed in a microtiter well with 50 ul of 2.5 N sulfuric acid and 50 ul of water. The absorbance at 450 nm was measured in a microtiter plate reader. The minimum detectable amount of biotinylated DNA was correlated to the copy number of capture probe used in the initial coating solution. The results are shown below.

15	CONCENTRATION OF <u>COATING SOL.</u>	<u>COPY #</u>	<u>Ave A₄₅₀</u>
	22 μ M	10 ¹⁵	0.907
	0.22 μ M	10 ¹³	0.808
20	0.22 nM	10 ¹⁰	0.176
	22 fM	10 ⁶	0.175
	0	0	0.017

Assuming a one to one correspondence of binding
25 between capture probe and target sequence, the copy number
should represent an estimation of the sensitivity of an
unoptimized assay for the detection of target sequence.

Other embodiments are within the following claims.

[illegible]